








Thermocouple temperature probe as per IEC 584-1, 2 and 3 standards for 2014 portable instruments

Probe	Size	Measuring range Probe with device accuracy	T ₉₉ **
-------	------	--	--------------------

Pipes

<p>Contact probe with velcro. Velcro fixing for Ø 100 mm maxi pipes with cable (Tc K).</p> <p>SKV 150 (cable length : 1.5 m) (17156) SKV 300 (cable length : 3 m) (17157) SKV 500 (cable length : 5 m) (17159)</p>		From -20 to +90 °C ±1.5 °C	50 s
<p>Contact probe with pliers for pipe Ø 10 to 35 mm with straight cable. (Tc K).</p> <p>SKCP (24811)</p>		From -40 to +125 °C ±1.5 °C	50 s
<p>Contact probe with lamella for pipe Ø 10 to 50 mm with spring handle and straight cable. (Tc K).</p> <p>SKCT (22226)</p>		From -40 to +150 °C ±1.5 °C	15 s
<p>Contact probe with lamella, curved tip for pipe from 10 to 50 mm with handle and coiled cable. (Tc K).</p> <p>SCTK 100 (24854)</p>	 <p>100 mm Ø13 mm</p>	From -40 to +250 °C ±1.5 °C	15 s

Contact




<p>Contact probe with circular end, with handle, coiled cable. (Tc K).</p> <p>SCK 150 (24647)</p>	 <p>150 mm Ø13 mm</p>	From -20 to +150 °C • ±1.5 °C* • ±4% of reading ±1.5 °C**	20 s
<p>Contact probe with copper circular end for reduced space, with handle, coiled cable. (Tc K).</p> <p>SCCK 150 (24855)</p>	 <p>150 mm Ø6 mm</p>	From -20 to +150 °C • ±1.5 °C* • ±4% of reading ±1.5 °C**	30 s
<p>Spring contact probe for reduced space with handle, coiled cable. (Tc K).</p> <p>SCRK150 (25111)</p>	 <p>150 mm Ø7 mm</p>	From -20 to +150 °C • ±1.5 °C* • ±4% of reading ±1.5 °C**	5 s
<p>Contact probe with lamella, direct output on handle, coiled cable. (Tc K).</p> <p>SCLK (24702)</p>	 <p>Ø15 mm</p>	From -40 to +150 °C ±1.5 °C	5 s
<p>Contact probe with lamella with handle and coiled cable. (Tc K).</p> <p>SCLK 150 (24648)</p>	 <p>150 mm Ø 15 mm</p>	From -40 to +250 °C ±1.5 °C	5 s
<p>Contact probe with lamella, angled at 90° with handle and coiled cable. (Tc K).</p> <p>SCLCK 150 (24649)</p>	 <p>150 mm Ø15 mm</p>	From -40 to +250 °C ±1.5 °C	5 s

Probe	Size	Measuring range Probe with device accuracy	T ₉₉ **
-------	------	--	--------------------

Contact (next)








<p>2-function probe : contact with lamella with reclining contact tip at 90° with handle and coiled cable. (Tc K).</p> <p>SCLK2 150 (24814)</p>	 <p>150 mm</p>	<p>From -40 to +250 °C ±1.5 °C</p>	5 s
<p>High temperature contact probe with lamella, with handle and coiled cable. (Tc K).</p> <p>SCLK-HT (24681)</p>	 <p>200 mm Ø27 mm</p>	<p>From -50 to +800 °C ±0.5 % of reading ±1.5 °C</p>	5 s
<p>Contact probe with magnetic lamella with straight cable. (Tc K).</p> <p>SCLAIK (24716)</p>		<p>From -40 to +250 °C ±1.5 °C</p>	5 s
<p>2-function probe : contact with lamella and reclining contact tip at 90° for surface measurement of moving part, straight cable. (Tc K).</p> <p>SCLAIK2-150 (24851)</p>	 <p>150 mm</p>	<p>From -40 to +250 °C ±1.5 °C</p>	5 s
<p>Probe for surface measurement of moving part. Aluminium contact element on casters with handle and coiled cable. (Tc K).</p> <p>SFCSMK (21254)</p>		<p>From 0 to +400 °C • ±1.5 °C* • ±4% of reading ±1.5 °C**</p>	4 s
<p>2-function probe : for surface measurement of moving part and reclining at 90°. Aluminium contact element on casters with handle and coiled cable. (Tc K).</p> <p>SFCSMK-2 (24815)</p>		<p>From 0 to +400 °C • ±1.5 °C* • ±4% of reading ±1.5 °C**</p>	4 s
<p>Contact probe for griddles. Hood mounting with contact tip with lamella. Shielded Teflon® cable under stainless steel hose output. (Tc K).</p> <p>SK-PC (22382)</p>	 <p>Ø63.5 mm</p>	<p>From -40 to +250 °C • ±1.5 °C* • ±4% of reading ±1.5 °C**</p>	5 s

Ambient

<p>Ambient probe, direct output on compensated male miniature connector. Without handle or cable. (Tc K).</p> <p>SKA-110 (17155)</p>	 <p>110 mm Ø4.5 mm</p>	<p>From -40 to +80 °C ±1.5 °C</p>	50 s
<p>Ambient probe with handle and coiled cable. (Tc K).</p> <p>SAK-150 (24646)</p>	 <p>150 mm Ø4.5 mm</p>	<p>From -40 to +250 °C ±1.5 °C</p>	50 s
<p>Ambient wired probe. Apparent welding, isolated Teflon® cable, output on compensated male miniature connector. (Tc K).</p> <p>SAK-05 (cable length : 0.5 m) (24816) SAK-1 (cable length : 1 m) (24817) SAK-2 (cable length : 2 m) (24818) SAK-5 (cable length : 5 m) (24819) SAK-10 (cable length : 10 m) (24820) SAK-25 (cable length : 25 m) (24821)</p>		<p>From -40 to +250 °C ±1.5 °C</p>	3 s






Probe	Size	Measuring range Probe with device accuracy	T ₉₉ **
-------	------	--	--------------------

Penetration

<p>Penetration probe. Stainless steel contact tip with pointed contact tip, handle and coiled cable. (Tc K).</p> <p><i>SPK 150 (24650)</i></p>	 <p>150 mm Ø 3 mm</p>	<p>From -40 to +250 °C ±1.5 °C</p>	30 s
<p>Penetration probe. Stainless steel contact tip with pointed contact tip, handle and coiled cable. (Tc K).</p> <p><i>SPK 300 (24823)</i></p>	 <p>300 mm Ø 4.5 mm</p>	<p>From -40 to +250 °C ±1.5 °C</p>	35 s
<p>Needle penetration probe. Stainless steel contact tip, with handle and straight cable. (Tc K).</p> <p><i>SPK 10 (24827)</i></p>	 <p>10 mm Ø 1.5 mm 10 mm</p>	<p>From -40 to +150 °C ±1.5 °C</p>	2 s
<p>IP65 protection corkscrew penetration probe . Stainless steel contact tip with corkscrew end, stainless steel T handle and shielded Teflon® cable. (Tc K).</p> <p><i>SKT 125 (17093)</i></p>	 <p>125 mm Ø 8 mm Ø 3.5 mm</p>	<p>From -40 to +250 °C ±1.5 °C</p>	50 s
<p>T handle IP65 protection penetration probe. Stainless steel contact tip with pointed end and shielded Teflon® cable. (Tc K).</p> <p><i>SKTA 125 (24824)</i></p>	 <p>125 mm Ø 3 mm</p>	<p>From -40 to +250 °C ±1.5 °C</p>	30 s
<p>IP65 protection robust penetration probe. Stainless steel contact tip with pointed end, stainless steel handle and straight cable. (Tc K).</p> <p><i>SPPK 125 (24826)</i></p>	 <p>Ø 3 mm 125 mm</p>	<p>From -40 to +250 °C ±1.5 °C</p>	30 s
<p>IP65 protection needle penetration probe. Stainless steel contact tip with needle end, stainless steel tube and straight cable. For thin measurement. (Tc K).</p> <p><i>SPAIK 80 (24828)</i></p>	 <p>Ø 1.3 mm 80 mm</p>	<p>From 0 to +250 °C ±1.5 °C</p>	2 s

Probe	Size	Measuring range Probe with device accuracy	T ₉₉ **
-------	------	--	--------------------









Special compost

<p>Special compost probe, stainless steel protection sheath with pointed end. T handle and output on coiled cable. (Tc K).</p> <p>SKP 1000 (1 m) (17160) SKP 1500 (1.5 m) (17161) SKP 2000 (2 m) (17163)</p>	 <p>Ø 21.3 mm</p>	<p>From -20 to +150 °C ±1.5 °C</p>	<p>165 s</p>
<p>Galvanized plate for compost probe. Possible fixing with anti-theft device KAV of KISTOCK dataloggers or magnetic fixing of protective housing. Factory mounting.</p> <p>KSP (14809)</p>		-	-
<p>Kit with a galvanized plate (KSP) for compost probe. Possible fixing with anti-theft device KAV of KISTOCK dataloggers or magnetic fixing of protective housing and mountings accessories. To install after delivery.</p> <p>KIT-KSP (24829)</p>		-	-
<p>IP 67 polycarbonate housing with transparent front and specific seal to resist in aggressive environment in EPDM. Processing and drilling performed for mounting on compost probe.</p> <p>BPK (20532)</p>		-	-
<p>Aluminium IP 65 housing with specific seal to resist in aggressive environment in neoprene. Processing and drilling performed for mounting on compost probe.</p> <p>BAK (22820)</p>		-	-


**Under application condition

Probe	Size	Measuring range Probe with device accuracy	T ₉₉ **
-------	------	--	--------------------

Immersion

Immersion probe. Stainless steel contact tip , with handle and coiled cable. (Tc K). <i>SIK 150 (24641)</i> <i>SIK 250 (24642)</i>	 150 mm 250 mm Ø 4.5 mm	From -40 to +250 °C ±1.5 °C	35 s
High temperature immersion probe. Inconel contact tip, with handle and coiled cable. (Tc K). <i>SIK 500 HT (24644)</i> <i>SIK 1000 HT (24645)</i>	 500 mm 1000 mm Ø 6 mm	From -40 to +1000 °C • From -40 to +375 °C : ±1,5 °C • Remaining range : ±0.4 % of reading	115 s
K thermocouple immersion probe high temperature. Inconel contact tip with stainless steel handle, coiled cable and compensated male miniature connector. (Tc K). <i>SIK 1500 HT (24979)</i> <i>SIK 2000 HT (24980)</i>	 1500 mm 2000 mm Ø 6 mm	From -40 to +1000 °C • From -40 to +375 °C : ±1,5 °C • Remaining range : ±0.4 % of reading	115 s
Very high temperature immersion probe. Ceramic contact tip with handle and straight cable . (Tc S). <i>SIS 1000 HT (24830)</i>	 Ø 8 mm 1000 mm	From 0 to +1400 °C • From 0 to 1100 °C : ±1 °C • From 1100 to 1400 °C : ±0.15 % of reading	/
Very low temperature immersion probe. Deformable lined contact tip with handle and coiled cable. (Tc T). <i>SIT 300 BT (24831)</i>	 Ø 1.5 mm 300 mm	From -200 to +50 °C • From -200 to -67 °C : ±1.5 % of reading • From -67 to -40 °C : ±1 °C • From -40 to +125 °C : ±0.5 °C	2 s
Immersion probe with direct output on compensated male miniature connector. Deformable lined contact tip. (Tc K). <i>SIKI 150 (24833)</i>	 Ø 1.5 mm 150 mm	From -40 to +700 °C • From -40 to +375 °C : ±1.5 °C • Remaining range : ±0.4 % of reading	2 s
Immersion probe with direct output on compensated male miniature connector. Deformable lined contact tip. (Tc K). <i>SIKI 300 (24832)</i>	 Ø 0.5 mm 300 mm	From -40 to +300 °C • ±1.5 °C	1 s
Immersion probe with direct output on compensated male miniature connector. Deformable lined contact tip. (Tc K). <i>SIKI 500 (24875)</i>	 Ø 3 mm 500 mm	From -40 to +1000 °C • From -40 to +375 °C : ±1.5 °C • Remaining range : ±0.4 % of reading	5 s








Extensions

Shielded PVC cable for temperature probes with compensated male/female miniature connector (Tc K). <i>RTCK-150 (1.5 m) (24834)</i> <i>RTCK-300 (3 m) (24835)</i> <i>RTCK-500 (5 m) (24836)</i>		From 0 to +100 °C	-
---	--	-------------------	---



Pt100 temperature probe as per IEC60751 standard for 2014 portable instruments

Probe	Size	Measuring range Probe with device accuracy	T ₉₉ **
-------	------	--	--------------------

Pt100 probe for class 50 and class 110 portable






<p>Ambient probe. Perforated stainless steel contact tip, with handle, coiled cable and connector</p> <p>SAP 150 (24656)</p>	 <p>150 mm Ø 4.5 mm</p>	<p>From -40 to +250 °C ±0.4 % of reading ±0.3 °C</p>	115 s
<p>Contact probe with circular end. Stainless steel contact tip, with handle, coiled cable and connector.</p> <p>SCP 150 (24657)</p>	 <p>150 mm Ø 13 mm</p>	<p>From -20 to +150 °C</p> <ul style="list-style-type: none"> • ±0.4 % of reading ±0.3 °C* • ±6 % of reading ±0.25 °C** 	150 s
<p>Immersion probe. Stainless steel contact tip, with handle, coiled cable and connector.</p> <p>SIP 150 (24658) SIP 250 (24659)</p>	 <p>150 mm 250 mm Ø 4.5 mm</p>	<p>From -40 to +250 °C ±0.4 % of reading ±0.3 °C</p>	35 s
<p>Low temperature immersion probe. Stainless steel contact tip, with handle, coiled cable and connector.</p> <p>SIP 300 BT (24852)</p>	 <p>300 mm Ø 4.5 mm</p>	<p>From -100 to +50 °C ±0.4 % of reading ±0.3 °C</p>	25 s
<p>High temperature immersion probe. Stainless steel contact tip, with handle, coiled cable and connector.</p> <p>SIP 500 HT (24853)</p>	 <p>500 mm Ø 6 mm</p>	<p>From -40 to +400 °C ±0.4 % of reading ±0.3 °C</p>	45 s
<p>Penetration probe. Stainless steel contact tip, with handle, coiled cable and connector.</p> <p>SPP 150 (24660)</p>	 <p>150 mm Ø 4.5 mm</p>	<p>From -40 to +250 °C ±0.4 % of reading ±0.3 °C</p>	35 s
<p>Needle penetration probe. Stainless steel contact tip, with stainless steel handle and cable with connector</p> <p>SPAI 90 (24843)</p>	 <p>Ø 2 mm 90 mm</p>	<p>From 0 to +200 °C ±0.4 % of reading ±0.3 °C</p>	15 s

Interchangeable Pt100 probe (SMART-2014) for class 210 and class 310 portable

<p>Ambient probe. Perforated stainless steel contact tip, integrated mini-DIN connector, SMART-2014 recognition system. Supplied with calibration certificate.</p> <p>SAPS 150 (24838)</p>	 <p>150 mm Ø 4.5 mm</p>	<p>From -40 to +250 °C ±0.3 % of reading ±0.25 °C</p>	115 s
<p>Contact probe with circular end. Stainless steel contact tip, integrated mini-DIN connector, SMART-2014 recognition system. Supplied with calibration certificate.</p> <p>SCPS 150 (24839)</p>	 <p>150 mm Ø 13 mm</p>	<p>From -20 to +150 °C</p> <ul style="list-style-type: none"> • ±0.3 % of reading ±0.25 °C* • ±6 % of reading ±0.25 °C** 	150 s





Probe	Size	Measuring range Probe with device accuracy	T ₉₉ **
-------	------	--	--------------------

Interchangeable Pt100 probes (SMART-2014) for class 210 and class 310 instruments (next)





<p>Ambient probe. Stainless steel contact tip with handle, integrated mini-DIN connector. SMART-2014 recognition system. Supplied with adjustment certificate.</p> <p>SIPS 150 (24840) SIPS 250 (24841)</p>		<p>From -40 to +250 °C ±0.3 % of reading ±0.25 °C</p>	35 s
<p>Very low temperature immersion probe. Stainless steel contact tip with handle, integrated mini-DIN connector. SMART-2014 recognition system. Supplied with adjustment certificate.</p> <p>SIPS 300 BT (24844)</p>		<p>From -200 to +50 °C</p> <ul style="list-style-type: none"> • From -100 to +50 °C : ±0.3 % of reading ±0.25 °C • Remaining range : ±0.6 % of reading ±0.25 °C 	25 s
<p>High temperature immersion probe. Stainless steel contact tip with handle, integrated mini-DIN connector. SMART-2014 recognition system. Supplied with adjustment certificate.</p> <p>SIPS 500 HT (24845)</p>		<p>From -40 to +450 °C ±0.3 % of reading ±0.25 °C</p>	45 s
<p>Penetration probe. Stainless steel contact tip with handle, integrated mini-DIN connector. SMART-2014 recognition system. Supplied with adjustment certificate.</p> <p>SPPS 150 (24842)</p>		<p>From -40 to +250 °C ±0.3 % of reading ±0.25 °C</p>	35 s
<p>Needle penetration probe. Stainless steel contact tip with handle, integrated mini-DIN connector. SMART-2014 recognition system. Supplied with adjustment certificate.</p> <p>SPAIS 90 (24895)</p>		<p>From 0 to +200 °C ±0.3% of reading ±0.25 °C</p>	15 s

Probe	Size	Measuring range Probe with device accuracy	T ₉₉ **
-------	------	--	--------------------

ACCURATE Pt100 probes (SMART-2014) for class 210 and class 310 instruments

<p>Accurate immersion probe. Stainless steel contact tip with handle, integrated mini-DIN connector. SMART-2014 recognition system. Supplied with 3 points calibration certificate.</p> <p>SPRP 300 (24846)</p> 		<p>From -200 to +500 °C</p> <ul style="list-style-type: none"> From -40 to +200 °C : ±0.15% of reading ±0.15 °C Remaining range : ±0.3 % of reading ±0.25 °C 	35 s
<p>Accurate immersion probe. Stainless steel contact tip with handle, integrated mini-DIN connector. SMART-2014 recognition system. Supplied with COFRAC (ISO 17025 standard) 3 points calibration certificate.</p> <p>SPRP 300 C (24847)</p> 		<p>From -200 to +500 °C</p> <ul style="list-style-type: none"> From -40 to +200 °C : ±0.15% of reading ±0.15 °C Remaining range : ±0.3 % of reading ±0.25 °C 	35 s

WIRELESS Pt100 probe (SMART-2014) for class 210 and class 310 instruments

<p>Wireless ambient temperature probe. Perforated stainless steel contact tip. Wireless transmission system with handle and multifunction button. Supplied with adjustment certificate.</p> <p>SAPF 150 (24793)</p>		<p>From -40 to +250 °C ±0.3 % of reading ±0.25 °C</p>	115 s
<p>Wireless contact temperature probe. Stainless steel contact tip with circular end. Wireless transmission system with handle and multifunction button. Supplied with adjustment certificate.</p> <p>SCPF 150 (24794)</p>		<p>From -20 to +150 °C</p> <ul style="list-style-type: none"> ±0.3% of reading ±0.25 °C* ±6 % of reading ±0.25 °C** 	150 s
<p>Wireless immersion temperature probe. Stainless steel contact tip, wireless transmission system with handle and multifunction button. Supplied with adjustment certificate.</p> <p>SIPF 150 (24795) SIPF 250 (24796)</p>		<p>From -40 to +250 °C ±0.3 % of reading ±0.25 °C</p>	35 s
<p>Wireless penetration temperature probe. Stainless steel contact tip with pointed end. Wireless transmission system with handle and multifunction button. Supplied with adjustment certificate.</p> <p>SPPF 150 (24797)</p>		<p>From -40 to +250 °C ±0.3 % of reading ±0.25 °C</p>	35 s

*Under laboratory condition / **Under application condition

www.kimo.fr

Distributed by :



EXPORT DEPARTMENT

Tel : + 33. 1. 60. 06. 69. 25 - Fax : + 33. 1. 60. 06. 69. 29

e-mail : export@kimo.fr